

Synergy Industrial Services Pvt. Ltd.

30/1, Ballygunge Place,
Kolkata – 700019, India

Mob:+91 7604008304

E-mail: sales@synergyispl.com

Web: www.synergyispl.com



Technical information sheet

Company :

Contact person :

Phone :

E-mail :

Vulcanizing Press for rubber conveyer belt:

Max Belt width in mm	Belt type (EP/STEEL CORD)	Belt Class e.g. EP 630/4 or ST 2000	Splice length as per belt supplier's recommendation *

*unless otherwise specified, we design on the basis of DIN recommendation of splice length.

Type of splice: (please highlight the required)

- Rhombic 16°42'
- Rhombic 22°
- Rectangular.

Type of Platen: (please highlight the required)

- Single.
- Combination with platens for edge repairs

Pressure System/Heating System:

(please highlight the required)

- Mechanical - W (Pressure Screw System)
- Hydraulic - WH (Hydraulic Cylinder System)

Cooling system: (please highlight the required)

- Normal :
- Compressed Air :

Kind of Electricity used:

- Voltage.
- Phase
- Frequency

Temperature Control Panel:

- AT 3- DIGITAL CONTROLLER without MULTIFUNCTION METER.
- AT 4- DIGITAL CONTROLLER with MULTIFUNCTION METER.
- AT 5- PLC Controlled with PC Interface